

# Chapter 1 - Creating Access to Back Office

## Creating Access to Back Office

First we are going to create an access to the web service.

To do this, simply go into your Back Office and click on the "Tools / Web Service" tab.

### Configuration



**Configuration**

Activer le service web  Oui  Non

Avant d'activer le service web, vous devez être certain :

1. d'être bien sur que le réécriture d'URL est supportée par le serveur
2. Assurez vous que les 4 méthodes GET, POST, PUT, DELETE and HEAD sont supportés par le serveur.

[Enregistrer](#)

Select "Enable Web Service" and click Save to activate the service.

## Generating a .htaccess file

To get the web service to work, you need to generate / regenerate a .htaccess file.

While still in the Back Office, go to the Tools / Generators tab and click:

[Générer le fichier .htaccess](#)

## Creating access

Return to Tools / Web Service

- Click "Add New", and you'll access the "passkey" permission and definition page.
- Click on "Generate". This will generate an authentication key.

Thanks to this key, you will be able to access the web service.



**Comptes Service Web**

Clé  [Générer!](#)

Clé du compte service web


Statut

**Permissions** Paramétrez les permissions :

Ressource	Voir (GET)	Modifier (PUT)	Ajouter (POST)	Supprimer (DELETE)	Aperçu (HEAD)
addresses	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
carriers	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
categories	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
combinations	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
countries	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
customers	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
groups	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Then you can create rights for each resource you want to access.

In the list of permissions, the left button allows you to define all the rights for a given resource. Select the resources you need to manipulate from your application; in our case check the first check box in the "customers" row and then press "Save".

 Please use the "Generate" button so that the key cannot be guessed.

If you define your own passkey, make sure it is very secure and that these rights are limited.