

Changes in version 1.5 which impact theme development

Table of content

- [Changes in version 1.5 which impact theme development](#)
 - [Foreword](#)
 - [getPageLink](#)
 - [B2B](#)
 - [Layered navigation](#)
 - [Product attributes](#)
 - [Changes to be applied to a 1.4 theme in order use per-combination unique product URLs](#)
 - [New cart summary](#)
 - [Social titles](#)
 - [New template](#)
 - [Dynamic template](#)
 - [General considerations theme URLs and form action](#)

Changes in version 1.5 which impact theme development

Foreword

A lot has changed between the Theme API in PrestaShop 1.4 and the one available in version 1.5. Wholes sections have been rewritten while others have been added, mostly to take into account new features from PrestaShop 1.5, such as the cart rules system et the partial delivery/multishipping one.

But in general, it is highly advisable not to adapt a 1.4 theme to PrestaShop, but rather start with the default theme and adapt your HTML and CSS files to it. This way, you will ensure that all the new features from PrestaShop 1.5 will be included in your theme out of the box.

getPageLink

The way `getPageLink()` works has been changed. The first parameter should no longer be the controller's file, but instead the controller name.

In 1.4:

```
{$link->getPageLink('order-slip.php', true)}
```

In 1.5:

```
{$link->getPageLink('order-slip', true)}
```

B2B

New fields are now available for the sign-up page. See `authentication.tpl` in the default theme.

```

{if $b2b_enable}
<fieldset class="account_creation">
  <h3>{l s='Your company information'}</h3>
  <p class="text">
    <label for="">{l s='Company'}</label>
    <input type="text" class="text" id="company" name="company" value="{if isset($smarty.post.
company)}{$smarty.post.company}{/if}" />
  </p>
  <p class="text">
    <label for="siret">{l s='SIRET'}</label>
    <input type="text" class="text" id="siret" name="siret" value="{if isset($smarty.post.siret)}
{$smarty.post.siret}{/if}" />
  </p>
  <p class="text">
    <label for="ape">{l s='APE'}</label>
    <input type="text" class="text" id="ape" name="ape" value="{if isset($smarty.post.ape)}{$smarty.
post.ape}{/if}" />
  </p>
  <p class="text">
    <label for="website">{l s='Website'}</label>
    <input type="text" class="text" id="website" name="website" value="{if isset($smarty.post.
website)}{$smarty.post.website}{/if}" />
  </p>
</fieldset>
{/if}

```

Layered navigation

Whenever possible, you should use the TPL files from the default theme, and refrain from editing them. This is true for all modules, but doubly so for the layered navigation one.

When adding layered navigation to a non-official theme, two things tend to break:

- The H1 tag update.
- The "available quantities" update.

You can fix these by following the following steps.

The H1 tag

In the `category.tpl` template file, you must add the `$categoryNameComplement` variable after the category name:

```

{$category->name|escape:'htmlall':'UTF-8'}
...becomes...
{$category->name|escape:'htmlall':'UTF-8'} {$categoryNameComplement|escape:'htmlall':'UTF-8'}

```

Available quantities

Still in `category.tpl`, you must remove the section displaying the number of products, and put it in a new template, named `category-count.tpl`.

For instance, with the default PrestaShop template:

```

<h1>
  {strip}
  {$category->name|escape:'htmlall':'UTF-8'} {$categoryNameComplement|escape:'htmlall':'UTF-8'}
  <span class="category-product-count">
    {if $category->id == 1 OR $nb_products == 0}{l s='There are no products.'}
    {else}
      {if $nb_products == 1}{l s='There is'}{else}{l s='There are'}{/if}
      {$nb_products}
      {if $nb_products == 1}{l s='product.'}{else}{l s='products.'}{/if}
    {/if}
  </span>
{/strip}
</h1>

```

...becomes...

```

<h1>
  {strip}
  {$category->name|escape:'htmlall':'UTF-8'} {$categoryNameComplement|escape:'htmlall':'UTF-8'}
  <span class="category-product-count">
    {include file="$tpl_dir./category-count.tpl"}
  </span>
{/strip}
</h1>

```

The new `category-count.tpl` template file contains the lines that were removed from `category.tpl`:

```

{if $category->id == 1 OR $nb_products == 0}{l s='There are no products.'}
{else}
  {if $nb_products == 1}{l s='There is'}{else}{l s='There are'}{/if}
  {$nb_products}
  {if $nb_products == 1}{l s='product.'}{else}{l s='products.'}{/if}
{/if}

```

Product attributes

Attribute types are now generic. Therefore, the way they are displayed has been changed in `product.tpl`.

In 1.4:

```

{if isset($groups)}
  <!-- attributes -->
  <div id="attributes">
    {foreach from=$groups key=id_attribute_group item=group}
      {if $group.attributes|@count}
        <p>
          <label for="group_{$id_attribute_group|intval}">{$group.name|escape:'htmlall':'UTF-8'} :</label>
          {assign var="groupName" value="group_{$id_attribute_group}"
          <select name="{ $groupName}" id="group_{ $id_attribute_group|intval}" onchange="javascript:
findCombination();{if $colors|@count > 0}$('#wrapResetImages').show('slow');{/if};">
            {foreach from=$group.attributes key=id_attribute item=group_attribute}
              <option value="{ $id_attribute|intval}" {if (isset($smarty.get.$groupName) &&
$smarty.get.$groupName|intval == $id_attribute) || $group.default == $id_attribute} selected="selected" {/if}
title="{ $group_attribute|escape:'htmlall':'UTF-8'}">{$group_attribute|escape:'htmlall':'UTF-8'}</option>
            {/foreach}
          </select>
        </p>
      {/if}
    {/foreach}
  </div>
{/if}

```

In 1.5:

```

{if isset($groups)}
  <!-- attributes -->
  <div id="attributes">
    {foreach from=$groups key=id_attribute_group item=group}
      {if $group.attributes|@count}
        <fieldset class="attribute_fieldset">
          <label class="attribute_label" for="group_{$id_attribute_group|intval}">{$group.
name|escape:'htmlall':'UTF-8'} </label>
          {assign var="groupName" value="group_{$id_attribute_group}" }
          <div class="attribute_list">
            {if ($group.group_type == 'select')}
              <select name="{ $groupName}" id="group_{ $id_attribute_group|intval}"
class="attribute_select" onchange="findCombination();getProductAttribute();{if $colors|@count >
0}$('#wrapResetImages').show('slow');{/if};">
                {foreach from=$group.attributes key=id_attribute
item=group_attribute}
                  <option value="{ $id_attribute|intval}" {if (isset
($smarty.get.$groupName) && $smarty.get.$groupName|intval == $id_attribute) || $group.default == $id_attribute}
selected="selected" {/if} title="{ $group_attribute|escape:'htmlall':'UTF-8'}">
                    { $group_attribute|escape:'htmlall':'UTF-8'}</option>
                    {/foreach}
                </select>
                {elseif ($group.group_type == 'color')}
                  <ul id="color_to_pick_list" class="clearfix">
                    {assign var="default_colorpicker" value="" }
                    {foreach from=$group.attributes key=id_attribute
item=group_attribute}
                      <li>
                        <a id="color_{ $id_attribute|intval}" class="color_pick
{if ($group.default == $id_attribute)} selected{/if}" style="background: { $colors.$id_attribute.value};" title="
{ $colors.$id_attribute.name}" onclick="colorPickerClick(this);getProductAttribute();{if $colors|@count >
0}$('#wrapResetImages').show('slow');{/if}">
                          {if file_exists
($col_img_dir|cat:$id_attribute|cat:'.jpg')}
                            <br>
                          {/if}
                        </a>
                      </li>
                      {if ($group.default == $id_attribute)}
                        { $default_colorpicker = $id_attribute}
                      {/if}
                    {/foreach}
                  </ul>
                  <input type="hidden" id="color_pick_hidden" name="{ $groupName}" value="
{ $default_colorpicker}" />
                {elseif ($group.group_type == 'radio')}
                  {foreach from=$group.attributes key=id_attribute item=group_attribute}
                    <input type="radio" class="attribute_radio" name="{ $groupName}"
value="{ $id_attribute}" {if ($group.default == $id_attribute)} checked="checked" {/if} onclick="
findCombination();getProductAttribute();{if $colors|@count > 0}$('#wrapResetImages').show('slow');{/if}">
                    { $group_attribute|escape:'htmlall':'UTF-8'}<br/>
                  {/foreach}
                {/if}
              </div>
            </fieldset>
          {/if}
        {/foreach}
      </div>
    {/if}
  }

```

Changes to be applied to a 1.4 theme in order use per-combination unique product URLs

There are only a couple of changes to apply, but they take quite a bit code. Fortunately, it is mostly copy/pasting of code we provide.

In product.tpl

The `product.tpl` has some changes that are need in its JavaScript code.

First, you have to add a call to the `getProductAttribute()` method on the `onClick` event of any `input` tag targeting attributes (select, radio or color). This method will be defined in the section.

You also need to add the following code this file's JavaScript section:

```
{if isset($attributesCombinations)}
// Combinations attributes informations
var attributesCombinations = new Array();
{foreach from=$attributesCombinations key=id item=aC}
    tabInfos = new Array();
    tabInfos['id_attribute'] = '{aC.id_attribute|intval}';
    tabInfos['attribute'] = '{aC.attribute}';
    tabInfos['group'] = '{aC.group}';
    tabInfos['id_attribute_group'] = '{aC.id_attribute_group|intval}';
    attributesCombinations.push(tabInfos);
{/foreach}
{/if}
```

In js/product.js

Here you should put the new `getProductAttribute()` method:

```

function getProductAttribute(){
    // get product attribute id
    product_attribute_id = $('#idCombination').val();
    product_id = $('#product_page_product_id').val();

    // get every attributes values
    request = '';
    //create a temporary 'tab_attributes' array containing the choices of the customer
    var tab_attributes = new Array();
    $('#div#attributes select, div#attributes input[type=hidden], div#attributes input[type=radio]:checked').each
(function(){
        tab_attributes.push($(this).val());
    });

    // build new request
    for (i in attributesCombinations)
        for (a in tab_attributes)
            if (attributesCombinations[i]['id_attribute'] == tab_attributes[a])
                request += '&'+attributesCombinations[i]['group']+ '=' + attributesCombinations[i]['attribute'];
    request = request.replace(request.substring(0, 1), '#');
    url = window.location+'';

    // redirection
    if (url.indexOf('#') != -1)
        url = url.substring(0, url.indexOf('#'));
    window.location = url+request;
}

$(document).ready(function(){
    url = window.location+'';
    // if we need to load a specific combination
    if (url.indexOf('#') != -1)
    {
        // get the params to fill
        params = url.substring(url.indexOf('#') + 1, url.length);
        tabParams = params.split('&');
        tabValues = new Array();
        for (i in tabParams)
            tabValues.push(tabParams[i].split('='));
        product_id = $('#product_page_product_id').val();
        // fill html with values
        $('.color_pick').removeClass('selected');
        count = 0;
        for (z in tabValues)
            for (a in attributesCombinations)
                if (attributesCombinations[a]['group'] == tabValues[z][0]
                    && attributesCombinations[a]['attribute'] == tabValues[z][1])
                {
                    count++;
                    // add class 'selected' to the selected color
                    $('#color_'+attributesCombinations[a]['id_attribute']).addClass('selected');
                    $('#input:radio[value='+attributesCombinations[a]['id_attribute']+']').attr('checked',
'checked');
                    $('#input:hidden[name=group_'+attributesCombinations[a]['id_attribute_group']+']').val
(attributesCombinations[a]['id_attribute']);
                    $('#select[name=group_'+attributesCombinations[a]['id_attribute_group']+']').val
(attributesCombinations[a]['id_attribute']);
                }
            // find combination
            if (count == tabValues.length)
                findCombination();
            // no combination found = removing attributes from url
            else
                window.location = url.substring(0, url.indexOf('#'));
        }
    });
}

```

New cart summary

This is a new addition to `order-payment.tpl`. See the original file from the default theme.

```
{if !$opc}
<div id="order-detail-content" class="table_block">
  <table id="cart_summary" class="std">
    <thead>
      <tr>
        <th class="cart_product first_item">{l s='Product'}</th>
        <th class="cart_description item">{l s='Description'}</th>
        <th class="cart_availability item">{l s='Avail.'}</th>
        <th class="cart_unit item">{l s='Unit price'}</th>
        <th class="cart_quantity item">{l s='Qty'}</th>
        <th class="cart_total last_item">{l s='Total'}</th>
      </tr>
    </thead>
    <tfoot>
      {if $use_taxes}
        {if $priceDisplay}
          <tr class="cart_total_price">
            <td colspan="5">{if $display_tax_label}{l s='Total products
(tax excl.):'}{else}{l s='Total products:'}{/if}</td>
            <td class="price" id="total_product">{displayPrice
price=$total_products}</td>
          </tr>
        {else}
          <tr class="cart_total_price">
            <td colspan="5">{if $display_tax_label}{l s='Total products
(tax incl.):'}{else}{l s='Total products:'}{/if}</td>
            <td class="price" id="total_product">{displayPrice
price=$total_products_wt}</td>
          </tr>
        {/if}
      {else}
        <tr class="cart_total_price">
          <td colspan="5">{l s='Total products:'}</td>
          <td class="price" id="total_product">{displayPrice
price=$total_products}</td>
        </tr>
      {/if}
      <tr class="cart_total_voucher" {if $total_discounts == 0}style="display: none;"{/if}>
        <td colspan="5">
          {if $use_taxes}
            {if $priceDisplay}
              {if $display_tax_label}{l s='Total vouchers (tax excl.):'}{else}
{l s='Total vouchers:'}{/if}
            {else}
              {if $display_tax_label}{l s='Total vouchers (tax incl.):'}{else}
{l s='Total vouchers:'}{/if}
            {/if}
          {else}
            {l s='Total vouchers:'}
          {/if}
        </td>
        <td class="price-discount price" id="total_discount">
          {if $use_taxes}
            {if $priceDisplay}
              {displayPrice price=$total_discounts_tax_exc}
            {else}
              {displayPrice price=$total_discounts}
            {/if}
          {else}
            {displayPrice price=$total_discounts_tax_exc}
          {/if}
        </td>
      </tr>
      <tr class="cart_total_voucher" {if $total_wrapping == 0}style="display: none;"{/if}>
        <td colspan="5">
```



```

                {if $use_taxes}
                    {if $priceDisplay}
                        {if $display_tax_label}{l s='Total gift-wrapping (tax excl.):'}
{else}{l s='Total gift-wrapping:'}{/if}
                    {else}
                        {if $display_tax_label}{l s='Total gift-wrapping (tax incl.):'}
{else}{l s='Total gift-wrapping:'}{/if}
                    {/if}
                {else}
                    {l s='Total gift-wrapping:'}
                {/if}
            </td>
            <td class="price-discount price" id="total_wrapping">
                {if $use_taxes}
                    {if $priceDisplay}
                        {displayPrice price=$total_wrapping_tax_exc}
                    {else}
                        {displayPrice price=$total_wrapping}
                    {/if}
                {else}
                    {displayPrice price=$total_wrapping_tax_exc}
                {/if}
            </td>
        </tr>
        {if $total_shipping_tax_exc <= 0 && !isset($virtualCart)}
            <tr class="cart_total_delivery">
                <td colspan="5">{l s='Shipping:'}</td>
                <td class="price" id="total_shipping">{l s='Free Shipping!'}</td>
            </tr>
        {else}
            {if $use_taxes}
                {if $priceDisplay}
                    <tr class="cart_total_delivery" {if $shippingCost <= 0} style="
display:none;"{/if}>
                        <td colspan="5">{if $display_tax_label}{l s='Total
shipping (tax excl.):'}{else}{l s='Total shipping:'}{/if}</td>
                        <td class="price" id="total_shipping">{displayPrice
price=$shippingCostTaxExc}</td>
                    </tr>
                {else}
                    <tr class="cart_total_delivery"{if $shippingCost <= 0} style="
display:none;"{/if}>
                        <td colspan="5">{if $display_tax_label}{l s='Total
shipping (tax incl.):'}{else}{l s='Total shipping:'}{/if}</td>
                        <td class="price" id="total_shipping" >{displayPrice
price=$shippingCost}</td>
                    </tr>
                {/if}
            {else}
                <tr class="cart_total_delivery"{if $shippingCost <= 0} style="display:
none;"{/if}>
                    <td colspan="5">{l s='Total shipping:'}</td>
                    <td class="price" id="total_shipping" >{displayPrice
price=$shippingCostTaxExc}</td>
                </tr>
            {/if}
        {/if}

        {if $use_taxes}
            <tr class="cart_total_price">
                <td colspan="5" id="cart_voucher" class="cart_voucher">
                    {if $voucherAllowed}
                        {if isset($errors_discount) && $errors_discount}
                            <ul class="error">
                                {foreach from=$errors_discount key=k item=error}
                                    <li>{ $error|escape:'htmlall':'UTF-8'}</li>
                                {/foreach}
                            </ul>
                        {/if}
                    {/if}
                </td>
            </tr>
        {/if}
    </td>

```

```

        <td colspan="2" class="price total_price_container" id="total_price_container">
            <p>{1 s='Total:'}</p>
            <span>{displayPrice price=$total_price}</span>
        </td>
    </tr>
    {else}
    <tr class="cart_total_price">
        <td colspan="5" id="cart_voucher" class="cart_voucher">
            {if $voucherAllowed}
            <div id="cart_voucher" class="table_block">
                {if isset($errors_discount) && $errors_discount}
                <ul class="error">
                    {foreach from=$errors_discount key=k item=error}
                    <li>{ $error|escape:'htmlall':'UTF-8'}</li>
                    {/foreach}
                </ul>
                {/if}
                {if $voucherAllowed}
                <form action="{if $opc}{ $link->getPageLink('order-opc.php', true)}{else}
                { $link->getPageLink('order.php', true)}{/if}" method="post" id="voucher">
                    <fieldset>
                        <h4><label for="discount_name">{1 s='Vouchers'}</label><
/h4>
                            <p>
                                <input type="text" id="discount_name" name="
discount_name" value="{if isset($discount_name) && $discount_name}{ $discount_name}{/if}" />
                            </p>
                            <p class="submit"><input type="hidden" name="
submitDiscount" /><input type="submit" name="submitAddDiscount" value="{1 s='ok'}" class="button" /></p>
                            {if $displayVouchers}
                            <h4 class="title_offers">{1 s='Take advantage of our
offers:'}</h4>
                                <div id="display_cart_vouchers">
                                    {foreach from=$displayVouchers item=voucher}
                                    <span onclick="{ $'#discount_name').val
('{$voucher.name}');return false;" class="voucher_name">{ $voucher.name}</span> - { $voucher.description} <br />
                                    {/foreach}
                                </div>
                                {/if}
                            </fieldset>
                        </form>
                    {/if}
                </div>
            {/if}
        </td>
        <td colspan="2" class="price total_price_container" id="total_price_container">
            <p>{1 s='Total:'}</p>
            <span id="total_price">{displayPrice price=$total_price_without_tax}<
/span>
        </td>
    </tr>
    {/if}
</tfoot>
<tbody>
{foreach from=$products item=product name=productLoop}
    {assign var='productId' value=$product.id_product}
    {assign var='productAttributeId' value=$product.id_product_attribute}
    {assign var='quantityDisplayed' value=0}
    {assign var='cannotModify' value=1}
    {assign var='odd' value=$product@iteration%2}
    {assign var='noDeleteButton' value=1}
    { * Display the product line *}
    {include file="$tpl_dir./shopping-cart-product-line.tpl"}
    { * Then the customized datas ones*}
    {if isset($customizedDatas.$productId.$productAttributeId)}
        {foreach from=$customizedDatas.$productId.$productAttributeId[$product.
id_address_delivery] key='id_customization' item='customization'}
            <tr id="product_{ $product.id_product}_{ $product.id_product_attribute}_
{ $id_customization}" class="alternate_item cart_item">
                <td colspan="4">
                    {foreach from=$customization.datas key='type'

```

```

item='datas'}

customizationUploaded">
    {if $type == $CUSTOMIZE_FILE}
        <div class="customizationUploaded">
            <ul class="
                {foreach from=$datas
                    <li>
                        
                    </li>
                }/foreach>
            </ul>
        </div>
    {elseif $type == $CUSTOMIZE_TEXTFIELD}
        <ul class="typedText">
            {foreach from=$datas
                <li>
                    {if $textField.
                        name}
                        {l s='%
s: ' sprintf=$textField.name}
                        {else}
                        {l
s='Text #s:' sprintf=$smarty.foreach.typedText.index+1}
                        {/if}
                    { $textField.
                        value}
                </li>
            }/foreach>
        </ul>
    {/if}
}foreach>
</td>
<td class="cart_quantity">
    {if isset($cannotModify) AND $cannotModify == 1}
        <span style="float:left">{if $quantityDisplayed
== 0 AND isset($customizedDatas.$productId.$productAttributeId)}
{ $customizedDatas.$productId.$productAttributeId|@count}{else}{ $product.cart_quantity-$quantityDisplayed}{/if}<
/span>
    {else}
        <div style="float:right">
            <a rel="nofollow" class="
cart_quantity_delete" id="{ $product.id_product}_{$product.id_product_attribute}_{$id_customization}" href="
{ $link->getPageLink('cart', true, NULL, "delete&id_product={ $product.id_product|intval}&ipa={ $product.
id_product_attribute|intval}&id_customization={ $id_customization}&token={ $token_cart} )" ></a>
        </div>
        <div id="cart_quantity_button" style="float:
left">
            <a rel="nofollow" class="cart_quantity_up" id="
cart_quantity_up_{ $product.id_product}_{$product.id_product_attribute}_{$id_customization}" href="{ $link-
>getPageLink('cart', true, NULL, "add&id_product={ $product.id_product|intval}&ipa={ $product.
id_product_attribute|intval}&id_customization={ $id_customization}&token={ $token_cart} )" >{l
s='Add'}"></a><br />
            {if $product.minimal_quantity < ($customization.
quantity -$quantityDisplayed) OR $product.minimal_quantity <= 1}
                <a rel="nofollow" class="cart_quantity_down"
id="cart_quantity_down_{ $product.id_product}_{$product.id_product_attribute}_{$id_customization}" href="{ $link-
>getPageLink('cart', true, NULL, "add&id_product={ $product.id_product|intval}&ipa={ $product.
id_product_attribute|intval}&id_customization={ $id_customization}&op=down&token={ $token_cart} )" >
title="{l s='Subtract'}">
                    
                </a>
            {else}
                <a class="cart_quantity_down" style="opacity:
0.3;" id="cart_quantity_down_{ $product.id_product}_{$product.id_product_attribute}_{$id_customization}" href="
# " title="{l s='Subtract'}">

```

```


</a>
{/if}
</div>
<input type="hidden" value="{ $customization.
quantity }" name="quantity_{ $product.id_product }_{ $product.id_product_attribute }_{ $id_customization }_hidden"/>
<input size="2" type="text" value="
{ $customization.quantity }" class="cart_quantity_input" name="quantity_{ $product.id_product }_{ $product.
id_product_attribute }_{ $id_customization }"/>
{/if}
</td>
<td class="cart_total"></td>
</tr>
{assign var='quantityDisplayed' value=$quantityDisplayed+$customization.
quantity}
{/foreach}
{* If it exists also some uncustomized products *}
{if $product.quantity-$quantityDisplayed > 0}{include file="$tpl_dir./shopping-
cart-product-line.tpl"}{/if}
{/if}
{/foreach}
{assign var='last_was_odd' value=$product@iteration%2}
{foreach $gift_products as $product}
{assign var='productId' value=$product.id_product}
{assign var='productAttributeId' value=$product.id_product_attribute}
{assign var='quantityDisplayed' value=0}
{assign var='odd' value=($product@iteration+$last_was_odd)%2}
{assign var='ignoreProductLast' value=isset
($customizedDatas.$productId.$productAttributeId)}
{assign var='cannotModify' value=1}
{* Display the gift product line *}
{include file="./shopping-cart-product-line.tpl" productLast=$product@last
productFirst=$product@first}
{/foreach}
</tbody>
{if count($discounts)}
<tbody>
{foreach from=$discounts item=discount name=discountLoop}
<tr class="cart_discount {if $smarty.foreach.discountLoop.last}last_item{elseif $smarty.
foreach.discountLoop.first}first_item{else}item{/if}" id="cart_discount_{ $discount.id_discount }">
<td class="cart_discount_name" colspan="2">{ $discount.name }</td>
<td class="cart_discount_description" colspan="3">{ $discount.description }</td>
<td class="cart_discount_price">
<span class="price-discount">
{if $discount.value_real > 0}
{if !$priceDisplay}
{displayPrice price=$discount.value_real*-1}
{else}
{displayPrice price=$discount.value_tax_exc*-1}
{/if}
{/if}
</span>
</td>
</tr>
{/foreach}
</tbody>
{/if}
</table>
</div>
{/if}

```

Social titles

Social titles, such as Mr or Ms, are now generic in PrestaShop 1.5. The authentication.tpl and identity.tpl files have been changed to take this into account.

In 1.4:

```
<input type="radio" name="id_gender" id="id_gender1" value="1"
  {if isset($smarty.post.id_gender) && $smarty.post.id_gender == 1}checked="checked"{/if} />
<label for="id_gender1" class="top">{l s='Mr.'}</label>
<input type="radio" name="id_gender" id="id_gender2" value="2"
  {if isset($smarty.post.id_gender) && $smarty.post.id_gender == 2}checked="checked"{/if} />
<label for="id_gender2" class="top">{l s='Ms.'}</label>
```

In 1.5:

```
{foreach from=$genders key=k item=gender}
  <input type="radio" name="id_gender" id="id_gender{$gender->id}" value="{ $gender->id}"
    {if isset($smarty.post.id_gender) && $smarty.post.id_gender == $gender->id}checked="checked"{/if} />
  <label for="id_gender{$gender->id}" class="top">{$gender->name}</label>
{/foreach}
```

New template

The file `layout.tpl` should be taken into account.

This file is defined (by default) as follows:

- Include *header.tpl* file (if we display the contents)
- Include the desired template file
- Include *footer.tpl* file (if we display the contents)
- Include "*Live Edit*"

You can modify the contents of this file based on an entity type or entity itself.

Type of entity

When you want to change the layout as an entity type such as categories, you can define a file `layout-EntityType.tpl` defined as follows:

```
{if !empty($display_header)}
  {include file='../header.tpl' HOOK_HEADER=$HOOK_HEADER}
{/if}
{* Your template start here *}
{if !empty($display_footer)}
  {include file='../footer.tpl'}
{/if}
{if !empty($live_edit)}
  {$live_edit}
{/if}
```

This file will be placed in: `/themes/default/override/layout-category.tpl` (For the category entity)

N.B.: a controller is an entity type. This means that you can use this feature for the supplier, stores, product, category, and many others entities.

By entity

When you want to change the layout according to a particular entity (e.g. for the product entity with ID 1) you can define a file `layout-EntityType-ID.tpl` defined as:

```

{if !empty($display_header)}
  {include file='../header.tpl' HOOK_HEADER=$HOOK_HEADER}
{/if}
{* Your template start here *}
{if !empty($display_footer)}
  {include file='../footer.tpl'}
{/if}
{if !empty($live_edit)}
  {$live_edit}
{/if}

```

This file will be placed in: `/themes/default/override/layout-product-1.tpl` (For the product entity with ID 1)

Dynamic template

It's possible to override the `getOverrideTemplate` from a `FrontController` to dynamically change the template.

General considerations theme URLs and form action

Many template files have been modified in the default theme in order to make use of the new feature of 1.5:

- **shopping-cart-product-line.tpl.** Many modifications in order to integrate multishipping and cart rules.
- **shopping-cart.tpl.** Many modification in order to integrate multishipping and cart rules.
- **order-address-multishipping-products.tpl.** Whole new template (multishipping).
- **order-address-multishipping.tpl.** Whole new template (multishipping).
- **order-address-product-line.tpl.** Whole new template (multishipping).
- **order-confirmation.tpl.** Links have been changed.
- **order-follow.tpl.** Links have been changed.
- **order-payment.tpl.** Added the cart summary.
- **order-return.tpl.** Various changes.
- **order-slip.tpl.** Links have been changed.
- **order-steps.tpl.** Links have been changed.
- **cart-summary.js.** the whole file has been rewritten. If you intend to update a 1.4 theme, you should directly use the 1.5 version.
- **order-opt.js.** Same as `cart-summary.js` above.
- **product.js.** Some ne JavaScript functions, such as `displayDiscounts(combination)`, `getProductAttribute()`, `colorPickerClick(elt)` or `checkUrl()`
- **tools.js.** Same as `cart-summary.js` above.
- **order-address.js.** Reworked to make use of multishipping.

order-address.tpl

Two new variables:

```

var addressMultishippingUrl = "{$link->getPageLink('address', true, NULL, "back={$back_order_page}?step=1
{'&multi-shipping=1'|urlencode}{if $back}&mod={$back|urlencode}{/if}")}";
var addressUrl = "{$link->getPageLink('address', true, NULL, "back={$back_order_page}?step=1{if $back}&mod=
{$back}{/if}")}";

```

End of main code block in 1.4:

```

{else}
  <div id="opc_account" class="opc-main-block">
    <div id="opc_account-overlay" class="opc-overlay" style="display:none;"></div>
{/if}

```

End of main code block in 1.5:

```

{else}
{if {Configuration::get('PS_ALLOW_MULTISHIPPING')} && !$cart->isVirtualCart()}
<div class="address-form-multishipping">
  <div class="button_multishipping_mode" id="multishipping_mode_box">
    <div class="title">{l s='Multi-shipping'}</div>
    <div class="description">
      <input type="checkbox" id="multishipping_mode_checkbox" onchange="multishippingMode(this); return
false;"/><label for="multishipping_mode_checkbox">{l s='I want to specify a delivery address for each product I
order.'}</label>
    </div>
    <div class="description_off">
      <a href="{ $link->getPageLink('order-opc', true, NULL, 'ajax=1&multi-
shipping=1&method=multishipping')}" id="link_multishipping_form" title="{l s='Choose the delivery addresses'}">
        {l s='Specify a delivery address for each product.'}
      </a>
    </div>
  </div>
</div>
<script type="text/javascript">
  {if $is_multi_address_delivery}
    var multishipping_mode = true;
  {else}
    var multishipping_mode = false;
  {/if}
  var open_multishipping_fancybox = {$open_multishipping_fancybox|intval};
</script>
</div>
{/if}
<div id="opc_account" class="opc-main-block">
<div id="opc_account-overlay" class="opc-overlay" style="display: none;"></div>
{/if}

```

order-carrier.tpl

The main data table has been heavily reworked, see the corresponding file in the default theme. You could also perform a diff on this file in its 1.4 and 1.5 incarnations, for instance using <http://www.quickdiff.com/>.

Note that the `HOOK_EXTRACARRIER` hook can now be used multiple times when multiple shipping is used:

- In 1.4:

Extract from order-carrier.tpl in v1.4

```

...
<tr id="HOOK_EXTRACARRIER">{ $HOOK_EXTRACARRIER}</tr>
...

```

- In 1.5:

Extract from order-carrier.tpl in v1.5

```
...
<div class="hook_extracarrier" id="HOOK_EXTRACARRIER_{\$id_address}">{if isset(\$HOOK_EXTRACARRIER_ADDR)
&& isset(\$HOOK_EXTRACARRIER_ADDR.\$id_address)}{\$HOOK_EXTRACARRIER_ADDR.\$id_address}{/if}</div>
{foreachelse}
<p class="warning" id="noCarrierWarning">
  {foreach \$cart->getDeliveryAddressesWithoutCarriers(true) as \$address}
    {if empty(\$address->alias)}
      {l s='No carriers available.'}
    {else}
      {l s='No carriers available for the address "%s".' sprintf=\$address->alias}
    {/if}
    {if !\$address@last}
      <br />
    {/if}
  {/foreach}
</p>
{/foreach}
...
```

order-detail.tpl

The following lines have been added in v1.5 in order to enable displaying the number of returned products directly in the order summary (order details):

```
{if \$order->hasProductReturned()}
  <th class="item">
    {l s='Returned'}
  </th>
{/if}
{if \$order->hasProductReturned()}
  <td>
    {\$product['qty_returned']}
  </td>
{/if}
```

The following new lines make it possible for your shop to give the customers details about the delivery, for instance its tracking number which can prove invaluable when multishipping is used.


```

<div class="table_block">
  {if $order->getShipping()|count > 0}
    <table class="std">
      <thead>
        <tr>
          <th class="first_item">{l s='Date'}</th>
          <th class="item">{l s='Carrier'}</th>
          <th class="item">{l s='Weight'}</th>
          <th class="item">{l s='Shipping cost'}</th>
          <th class="last_item">{l s='Tracking number'}</th>
        </tr>
      </thead>
      <tbody>
        {foreach from=$order->getShipping() item=line}
          <tr class="item">
            <td>{$line.date_add}</td>
            <td>{$line.state_name}</td>
            <td>{if $line.weight > 0}{$line.weight|string_format:"%.3f"} {Configuration::get('PS_WEIGHT_UNIT')}
          {else}-{/if}</td>
            <td>{if $order->getTaxCalculationMethod() == $smarty.const.PS_TAX_INC}{displayPrice price=$line.
shipping_cost_tax_incl currency=$currency->id}{else}{displayPrice price=$line.shipping_cost_tax_excl
currency=$currency->id}{/if}</td>
            <td>
              <span id="shipping_number_show">{if $line.tracking_number}{if $line.url && $line.tracking_number}<a
href="{ $line.url|replace: '@':$line.tracking_number }">{$line.tracking_number}</a>{else}{ $line.tracking_number}{
/if}{else}-{/if}</span>
            </td>
          </tr>
        {/foreach}
      </tbody>
    </table>
  {/if}
</div>

```

order-opc.tpl

New 'back' parameter added to addressUrl JavaScript variable:

```

{if $opc}
  {assign var="back_order_page" value="order-opc.php"}
{else}
  {assign var="back_order_page" value="order.php"}
{/if}

...then in the JavaScript code:

var addressUrl = '{ $link->getPageLink("address", true, NULL, "back={$back_order_page} ) }';

```

Also, the file has a new JavaScript variable:

```

var txtSelectAnAddressFirst = "{l s='Please start by selecting an address'}";

```